BMW Media information 03/2024

Page 1

Technical specifications. BMW X2. X2 xDrive20d.



		BMW X2 xDrive20d
		DHW AE ABHVEZOU
Body		
No. of doors / seats		5/5
Length/width/height (unladen)	mm	4554 / 1845 / 1590
Wheelbase	mm	2692
Track, front/rear	mm	1574 / 1575
Ground clearance	mm_	207 11.7
Turning circle Fuel tank capacity	m approx. l	
Engine oil 1)	upprox. i	6.5
Weight, unladen, to DIN/EU	kg	1705 / 1780
Max. load to DIN	kg	575
Max. permissible weight	kg	2280
Max. axle load, front/rear	kg	1165 / 1165
Max. trailer load		
braked (12%)/unbraked	kg	2000 / 750
Max. roofload/towbar download	kg	75 / 80
Luggage comp. capacity	Ī	560 – 1470
Air resistance	C _X	0.27
Power Unit		
Engine technology		BMW TwinPower Turbo technology: multi-stage turbocharging, high-
5 51		and low-pressure turbochargers with variable intake geometry,
		common-rail direct injection with solenoid injectors (max. injection
	р	ressure: 2500 bar), 48V mild hybrid technology using an electric moto
		integrated into the transmission
Max. output, overall 23	kW/hp	120 / 163
Max. torque, overall 2)	Nm	400
Diesel Engine		
Config./No. of cyls./valves		In-line / 4 / 4
Effective capacity	СС	1995
Stroke/bore	mm	90.0 / 84.0
Compression ratio	:1	16.5
Fuel		Diesel
Nominal power	kW/hp	110 / 150
at	rpm	4000
Nominal torque	Nm	360
at	rpm	1500 – 2500
Output per litre	kW/l	55.1
Electric Motor		
Nominal power	kW/hp	15 / 20
Nominal torque	Nm	55
Electrical System		
12V battery/installation	Ah/-	60 / engine compartment
48V battery/installation	Ah/-	20 / luggage compartment
Driving Dynamics and Safety		
Suspension, front	S	Single-joint spring strut axle in lightweight aluminium-steel construction
Suspension, rear		Three-link axle in lightweight steel construction
Brakes, front		Single-piston floating-calliper disc brakes
Brakes, rear		Single-piston floating-calliper disc brakes
Driving stability systems		Standard: DSC incl. ABS and DTC (Dynamic Traction Control),
		ARB technology (near-actuator wheel slip limitation), CBC (Cornering
	E	Brake Control), DBC (Dynamic Brake Control), Performance Control, Dry
		Braking function, fading compensation, drive-off assistant, trailer
		stability control, DSC networked with xDrive all-wheel-drive system;
Safaty aquipment		optional: adaptive M suspension Standard: airbags for driver and front passenger, side airbags for driver
Safety equipment	2	standara: airbags for ariver and front passenger, side airbags for ariver and front passenger, head airbags front and rear, interaction airbag
		between driver and front passenger, three-point inertia-reel seatbelts
		on all seats with belt tensioner and belt force limiter at the front, crash
		sensors, tyre pressure indicator
Steering		Electric Power Steering (EPS)
-		with Servotronic function, optional: M sport steering
Steering ratio, overall	:1	15.5
Tyres, front/rear		225/55 R18 102Y XL
Rims, front/rear		7.5J x 18 light-alloy

			BMW X2 xDrive20d
Transmission Type of transm	nission		Seven-speed Steptronic transmission with double clutch
Gear ratios	11331011	:1	15.870
deal latios	<u>'</u> -	: <u>-</u> :1	9.302
-	<u>"</u> 	: <u>-</u> :1	5.735
	III	:1 :1	4.015
	V	:1 :1	3.108
	<u> </u>		
	VI	:1	2.487
	VII	:1	2.016
	R	:1	14.255
Performance			
Power-to-weig	ht ratio (DIN)	kg/kW	14.2
Acceleration	0–100 km/h	s	8.6
Top speed		km/h	207
DMM Efficient	Domamiaa		
BMW Efficient			70V -916 6 10 -1 -1 - D. 1 - E D 91
BMW Efficientl standard featu			48V mild hybrid technology, Brake Energy Regeneration with recuperation display, Electric Power Steering, Automatic Start/Stop function, Optimum Shift Indicator, PERSONAL and EFFICIENT mode with coasting function, Proactive Driving Assistant,
			MW EfficientLightweight, optimised aerodynamic attributes, active air ap control, on-demand operation of ancillary units, map-regulated oil
		p	oump, efficiency-optimised all-wheel drive, differential with optimised
			warm-up behaviour, tyres with reduced rolling resistance,
			BMW Blue Performance technology with SCR catalytic converter
Fuel Consump	tion FCF		
Combined (WL		1/100	5.2 – 4.8
Combined (NE		1/100	
CO ₂ (WLTP)	-,	g/km	136 – 125
CO ₂ (NEDC)		g/km	-
Emission ratin	9		Euro 6e

Specifications apply to ACEA markets/data relevant to homologation applies in part only to Germany (weight)

Fuel consumption, CO_2 emission figures and power consumption as well as electric range were measured using the methods required according to Regulation VO (EC) 715/2007 as amended. Where a range is shown, the WLTP figures take into account the impact of any optional extras.

For vehicles which have been newly type-approved since 01.01.2021, official figures are only available according to WLTP. In addition, according to EU Regulation 2022/195, from 01.01.2023 the NEDC values in the EC certificates of conformity will no longer apply. Further information on the WLTP and NEDC measurement procedures is also available at www.bmw.de/wltp.

For further details of the official fuel consumption figures and official specific CO_2 emissions of new cars, please refer to the "Manual on the fuel consumption, CO_2 emissions and power consumption of new cars", available at sales outlets free of charge, from Deutsche Automobil Treuhand GmbH (DAT), Hellmuth-Hirth-Str. 1, 73760 Ostfildern-Scharnhausen and at https://www.dat.de/co2/.

¹⁾ Oil change

²⁾ Developed by the combination of the combustion engine (stated nominal figure) and the electric motor (up to stated nominal figure)